



FIRE ENGINE BOOSTER HOSES FOR THE FIRE FIGHTING INDUSTRY

Introducing the Alarm® Booster Hose: the epitome of reliability and durability. Manufactured and assembled in America, this rugged hose is designed to thrive in the harshest conditions. With multiple spiral reinforcement using aramid yarns and a specially formulated NBR/PVC* cover, it resists abrasion and weathering, ensuring longevity. The smooth black synthetic NBR/PVC rubber inner tube guarantees flexibility and enables a powerful flow. Trust the Alarm® Booster Hose to deliver unwavering performance, no matter the challenge.

We meticulously assemble hoses in compliance with the latest edition of NFPA 1961 and US Coast Guard (USCG) standards, undergoing rigorous quality assurance testing within our certified system.

*For 1-1/2" ID hose, cover is red EPDM



FIRE HOSE INDUSTRY EXPERTS



www.spartanindustrial.com



(985) 873-7959

THERMOID ALARM® BOOSTER - THERMOCURE FIRE ENGINE BOOSTER HOSE FOR THE FIRE FIGHTING INDUSTRY

Crafted to endure the harshest conditions, the Thermoid Alarm® Booster hose guarantees top-notch performance when it matters most – during a fire. When provided as an assembly, rest assured that the hose has been assembled and tested to meet NFPA 61 and USCG standards, ensuring its reliability in crucial situations.

Don't leave anything to chance when it comes to the safety of your team and the effectiveness of your firefighting operations. Contact us today to learn more about how you can trust the Thermoid Alarm® Booster – Thermocure Fire Engine Booster Hose for unmatched dependability.



THERMOID ALARM® BOOSTER FIRE ENGINE BOOSTER HOSE

THERMOID ALARM® BOOSTER HOSE



THERMOID ALARM® BOOSTER HOSE CONSTRUCTION:

- Cover Color: Red
- Oil Resistance: Medium, high
- Tube: NBR/PVC, RMA Class A
- Cover: NBR/PVC, RMA Class A, 1-1/2" I.D. EPDM
- Reinforcement: 2-spiral aramid yarn
- Temperature Range:
 - o -20°F to +190°F, 1-1/2" I.D. -40°F to +190°F
 - o -29°C to +88°C, 1-1/2" I.D. -40°C to +88°C
- Size: 3/4" to 1-1/2"

NOMINAL ID (INCH)	NOMINAL OD (INCH)	REINFORCEMENT SPIRALS	Working Pressure (PSI)	Minimum Bend Radius	Weight (lb/ft)
3/4	1.19	2	800	4.5	.41
1	1.5	2	800	7	.51
1 1/2	2	4	250	10.5	.71

PREMIUM THERMOID ALARM® BOOSTER THERMOCURE FIRE ENGINE BOOSTER HOSE

- Ultra-Tough
- Flexible
- Versatile
- Reliable
- Made in the USA
- Assemblies tested to meet NFPA 61 and USCG standards

REQUEST A QUOTE