

10041 RUBBER WATER SUCTION AND DISCHARGE



This heavy-duty water suction and discharge hose is engineered for the rigorous demands of construction, dewatering, agriculture, and industrial applications. It features an abrasion-resistant cover for durability in harsh conditions, including ozone exposure.

The high-quality synthetic rubber inner tube ensures chemical resistance, making it ideal for water transfer tasks with residual chemicals. Offering exceptional durability and reliability, Rubberworx 10041 is a dependable choice for challenging industrial tasks.

TUBE	Black Synthetic Rubber
REINFORCEMENT	Spiral Ply Textile
REINFORCEMENT HELIX	Steel Wire
COVER	Black Synthetic Rubber
TEMPERATURE	-13°F to 158°F
BRANDING EXAMPLE	RUBBERWORX 4" WATER SUCTION AND DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS	Roll or cut length wrapped in plastic for shipping

PART #	ID			OD			WP		BEND RADIUS		VACUUM PRESSURE	WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	Decimal (in)	Metric (mm)	inHg	(lb/ft)	(kg/m)	
10041-100	1	1.00	25	1 42/64	1.38	35	150	10	4	102	28	0.54	0.36	100
10041-125	1 1/4	1.25	32	1 24/64	1.65	42	150	10	5	127	28	0.65	0.43	100
10041-150	1 1/2	1.50	38	1 57/64	1.89	48	150	10	6	152	28	0.75	0.50	100
10041-200	2	2.00	51	2 28/64	2.44	62	150	10	9	229	28	1.01	0.68	100
10041-250	2 1/2	2.50	64	2 61/64	2.95	75	150	10	10	254	28	1.32	0.89	100
10041-300	3	3.00	76	3 32/64	3.46	88	150	10	14	356	28	1.61	1.08	100
10041-400	4	4.00	102	4 36/64	4.57	116	150	10	19	483	28	2.22	1.49	20, 100
10041-600	6	6.00	152	6 47/64	6.73	171	150	10	29	737	26	4.50	3.03	20, 100
10041-800	8	8.00	203	8 50/64	8.78	223	150	10	32	813	22	7.53	5.06	20, 100
10041-1000	10	10.00	254	10 56/64	10.88	276	150	10	44	1118	18	10.83	7.28	20
10041-1200	12	12.00	305	12 56/64	12.87	327	150	10	50	1270	15	12.44	8.36	20