

10051 WATER DISCHARGE



Rubberworx 10051 water discharge hose is designed for demanding environments like construction, dewatering, agriculture, and industrial use. With an abrasion- and ozone-resistant cover, it withstands harsh conditions.

The premium synthetic rubber tube handles residual chemicals, ensuring reliable performance in chemically aggressive situations. This hose offers durability, chemical resistance, and versatility, making it an ideal choice for challenging water discharge tasks.

TUBE	Black Synthetic Rubber
REINFORCEMENT	Spiral 2-Ply Textile
COVER	Black Synthetic Rubber Blend
TEMPERATURE	-13°F to 158°F
BRANDING EXAMPLE	RUBBERWORX 2" WATER DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS	Roll or Cut Length wrapped in plastic for shipping

PART #	ID			OD			WP		WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	(lb/ft)	(kg/m)	
10051-150	1 1/2	1.50	38	1 49/64	1.77	45	150	10	0.54	0.80	100
10051-200	2	2.00	51	2 18/64	2.28	58	150	10	0.63	0.94	100
10051-250	2 1/2	2.50	64	2 49/64	2.76	70	150	10	0.81	1.20	100
10051-300	3	3.00	76	3 17/64	3.27	83	150	10	1.01	1.50	20,100
10051-400	4	4.00	102	4 19/64	4.29	109	150	10	1.48	2.20	20,100
10051-500	5	5.00	127	5 25/64	5.39	137	150	10	2.55	3.80	20,100
10051-600	6	6.00	152	6 24/64	6.38	162	150	10	3.02	4.50	20,100
10051-800	8	8.00	203	8 35/64	8.54	217	150	10	4.10	6.10	20,60