

10091 BLUE PVC DISCHARGE



This light-duty blue PVC water discharge hose is versatile for construction, dewatering, agriculture, and industrial use. With a durable, chemical-resistant PVC tube and cover, it handles residual chemicals in water transfer operations. It's the ideal choice for light-duty discharge tasks.

~

TUBE	Blue PVC
REINFORCEMENT	Spiral Textile
COVER	Blue PVC
TEMPERATURE	-5°F to 170°F
BRANDING EXAMPLE	RUBBERWORX 2" PVC DISCHARGE 80 PSI
PACKAGING SPECIFICATIONS	Roll or Cut Length wrapped in plastic for shipping

PART #	ID			OD			WP		WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	(lb/ft)	(kg/m)	
10091-075	3/4	0.75	19	56/64	0.87	22	100	7	0.08	0.12	50, 100, 300
10091-100	1	1.00	25	1 8/64	1.13	29	85	6	0.10	0.15	50, 100, 300
10091-125	1 1/4	1.25	32	1 23/64	1.36	35	85	6	0.12	0.18	50, 100, 300
10091-150	1 1/2	1.50	38	1 47/64	1.73	44	80	6	0.19	0.28	50, 100, 300
10091-200	2	2.00	51	2 13/64	2.21	56	80	6	0.24	0.36	50, 100, 300
10091-250	2 1/2	2.50	64	2 43/64	2.68	68	70	5	0.30	0.45	50, 100, 300
10091-300	3	3.00	76	3 13/64	3.20	81	70	5	0.36	0.54	50, 100, 300
10091-400	4	4.00	102	4 17/64	4.26	108	70	5	0.53	0.79	50, 100, 300
10091-500	5	5.00	127	5 14/64	5.21	132	50	3	0.63	0.94	50, 100, 300
10091-600	6	6.00	152	6 20/64	6.31	160	50	3	0.86	1.28	50, 100, 300
10091-800	8	8.00	203	8 18/64	8.27	210	35	2	1.30	1.93	50, 100
10091-1000	10	10.00	254	10 21/64	10.32	262	35	2	1.88	2.80	50, 100
10091-1200	12	12.00	305	12 22/64	12.34	313	35	2	2.43	3.62	50, 100

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.



888-661-1680



www.rubberworxhose.com



sales@rubberworxhose.com