

10101 RED PVC DISCHARGE



This Brick Red PVC water discharge hose is designed for demanding environments, offering durability, chemical resistance, and reliable performance.

The reinforced construction ensures it can handle tough tasks while maintaining flexibility and ease of use across construction, dewatering, agricultural, and industrial applications.

TUBE	Brick Red PVC
REINFORCEMENT	Spiral Textile
COVER	Brick Red PVC
TEMPERATURE	-5°F to 170°F
BRANDING EXAMPLE	RUBBERWORX 3" PVC DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS	Roll or Cut Length wrapped in plastic for shipping

PART #	ID			OD			WP		WEIGHT		PACKAGING (ft)
	Fraction (in)	Decimal (in)	Metric (mm)	Fraction (in)	Decimal (in)	Metric (mm)	PSI	Bar	(lb/ft)	(kg/m)	
10101-150	1 1/2	1.50	38	1 50/64	1.78	45	150	10	0.29	0.43	100
10101-200	2	2.00	51	2 25/64	2.39	61	150	10	0.34	0.51	100
10101-250	2 1/2	2.50	64	2 49/64	2.77	88	150	10	0.41	0.61	100
10101-300	3	3.00	76	3 29/64	3.46	88	150	10	0.55	0.82	100
10101-400	4	4.00	102	4 36/64	4.56	116	150	10	0.85	1.26	100
10101-600	6	6.00	152	6 51/64	6.80	173	150	10	1.33	1.98	100
10101-800	8	8.00	203	8 21/64	8.32	211	150	10	1.62	2.41	100