



2C012 PETROLEUM COMPOSITE



This heavy-duty suction and discharge composite hose is designed for use in petroleum transfer applications. The flexible design is perfect for tank farms, midstream pumping locations, loading stations, loading arm hoses. In applications where bend radius and weight are an issue with rubber, petroleum composite is the perfect solution.

TUBE:	Polypropylene Film
REINFORCEMENT:	Polypropylene Fabric
COVER:	Blue PVC injected Fabric
TEMPERATURE:	-40°F to 212°F
INNER HELIX:	Galvanized
OUTER HELIX:	Galvanized

PART #	ID (IN)	OD (IN)	WP (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
2C012-100	1.00	1.12	250	4.00	29	0.61	10', 20', 25', 30'
2C012-150	1.50	1.68	250	5.50	29	1.00	10', 20', 25', 30'
2C012-200	2.00	2.24	250	7.00	29	1.46	10', 20', 25', 30'
2C012-300	3.00	3.36	250	8.70	29	2.47	10', 20', 25', 30'
2C012-400	4.00	4.40	250	16.00	29	3.55	10', 20', 25', 30'
2C012-600	6.00	6.75	250	23.00	29	8.00	10', 20', 25', 30'
2C012-800	8.00	9.00	250	32.00	29	10.65	10', 20', 25', 30'
2C012-1000	10.00	11.50	250	40.00	29	12.83	10', 20', 25', 30'
2C012-1200	12.00	13.00	250	48.00	29	15.15	10', 20', 25', 30'