

8C012 GENERAL CHEMICAL COMPOSITE



This heavy-duty suction and discharge composite hose is designed for use in general chemical transfer applications. The flexible design is perfect for tank farms, midstream pumping locations, loading stations, and loading arm hoses. In applications where bend radius and weight are an issue with rubber, chemical composite is the perfect solution.

TUBE:	Polypropylene Film
REINFORCEMENT:	Polypropylene Fabric
COVER:	Blue PVC injected Fabric
TEMPERATURE:	-40°F to 212°F
INNER HELIX:	Galvanized
OUTER HELIX:	Poly Coated Steel

PART #	ID (IN)	OD (IN)	WP (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
8C012-100	1.00	1.12	250	6.00	29	1.60	10', 20', 25', 30'
8C012-150	1.50	1.68	250	8.00	29	14.50	10', 20', 25', 30'
8C012-200	2.00	2.24	250	6.00	29	16.75	10', 20', 25', 30'
8C012-300	3.00	3.36	250	8.00	29	2.40	10', 20', 25', 30'
8C012-400	4.00	4.40	250	14.20	29	1.60	10', 20', 25', 30'
8C012-600	6.00	6.75	250	22.00	29	2.40	10', 20', 25', 30'
8C012-800	8.00	9.00	250	30.00	29	3.20	10', 20', 25', 30'
8C012-1000	10.00	11.50	250	40.00	29	7.20	10', 20', 25', 30'
8C012-1200	12.00	13.00	250	47.00	29	11.00	10', 20', 25', 30'