

SCHEDULE 40

FITTING CONNECTION TYPE:

Stub End Type A

PIPE SCHEDULE:

40

FITTING SIDE A TYPE:

Turnback

FITTING SIDE B TYPE:

Butt Weld

MATERIALS
STANDARDS:

304/316 Stainless Steel:
ASTM A403

Carbon Steel:
ASTM A234 WPB

Part Number	Material	NPS (in)	Outside Diameter (in) W	Flange Diameter (in) D	Length (in) L	Radius* (in) R	Inside Diameter (in) ID	Wall Thickness (in) T	Weight Each (lb)
RBX-STUBA-SCD40-100-304	304 Stainless Steel	1"	1.315	2.000	2.000	1/8	1.049	0.133	0.380
RBX-STUBA-SCD40-100-316	316 Stainless Steel	1"	1.315	2.000	2.000	1/8	1.049	0.133	0.380
RBX-STUBA-SCD40-100-CS	Carbon Steel	1"	1.315	2.000	2.000	1/8	1.049	0.133	0.380
RBX-STUBA-SCD40-125-304	304 Stainless Steel	1-1/4"	1.660	2.500	2.000	3/16	1.380	0.140	0.550
RBX-STUBA-SCD40-125-316	316 Stainless Steel	1-1/4"	1.660	2.500	2.000	3/16	1.380	0.140	0.550
RBX-STUBA-SCD40-125-CS	Carbon Steel	1-1/4"	1.660	2.500	2.000	3/16	1.380	0.140	0.550
RBX-STUBA-SCD40-150-304	304 Stainless Steel	1-1/2"	1.900	2.875	2.000	1/4	1.610	0.145	0.690
RBX-STUBA-SCD40-150-316	316 Stainless Steel	1-1/2"	1.900	2.875	2.000	1/4	1.610	0.145	0.690
RBX-STUBA-SCD40-150-CS	Carbon Steel	1-1/2"	1.900	2.875	2.000	1/4	1.610	0.145	0.690
RBX-STUBA-SCD40-200-304	304 Stainless Steel	2"	2.375	3.625	2.500	1/3	2.067	0.154	1.350
RBX-STUBA-SCD40-200-316	316 Stainless Steel	2"	2.375	3.625	2.500	5/16	2.067	0.154	1.350
RBX-STUBA-SCD40-200-CS	Carbon Steel	2"	2.375	3.625	2.500	5/16	2.067	0.154	1.350
RBX-STUBA-SCD40-250-304	304 Stainless Steel	2-1/2"	2.875	4.125	2.500	5/16	2.469	0.203	1.770
RBX-STUBA-SCD40-250-316	316 Stainless Steel	2-1/2"	2.875	4.125	2.500	5/16	2.469	0.203	1.770
RBX-STUBA-SCD40-250-CS	Carbon Steel	2-1/2"	2.875	4.125	2.500	5/16	2.469	0.203	1.770
RBX-STUBA-SCD40-300-304	304 Stainless Steel	3"	3.500	5.000	2.500	3/8	3.068	0.216	2.500
RBX-STUBA-SCD40-300-316	316 Stainless Steel	3"	3.500	5.000	2.500	3/8	3.068	0.216	2.500
RBX-STUBA-SCD40-300-CS	Carbon Steel	3"	3.500	5.000	2.500	3/8	3.068	0.216	2.500
RBX-STUBA-SCD40-400-304	304 Stainless Steel	4"	4.500	6.188	3.000	7/16	4.026	0.237	4.130
RBX-STUBA-SCD40-400-316	316 Stainless Steel	4"	4.500	6.188	3.000	7/16	4.026	0.237	4.130
RBX-STUBA-SCD40-400-CS	Carbon Steel	4"	4.500	6.188	3.000	7/16	4.026	0.237	4.130
RBX-STUBA-SCD40-600-304	304 Stainless Steel	6"	6.625	8.500	3.500	1/2	6.065	0.280	7.880
RBX-STUBA-SCD40-600-316	316 Stainless Steel	6"	6.625	8.500	3.500	1/2	6.065	0.280	7.880
RBX-STUBA-SCD40-600-CS	Carbon Steel	6"	6.625	8.500	3.500	1/2	6.065	0.280	7.880
RBX-STUBA-SCD40-800-304	304 Stainless Steel	8"	8.625	10.625	4.000	1/2	7.981	0.322	13.380
RBX-STUBA-SCD40-800-316	316 Stainless Steel	8"	8.625	10.625	4.000	1/2	7.981	0.322	13.380
RBX-STUBA-SCD40-800-CS	Carbon Steel	8"	8.625	10.625	4.000	1/2	7.981	0.322	13.380
RBX-STUBA-SCD40-1000-304	304 Stainless Steel	10"	10.750	12.750	5.000	1/2	10.020	0.365	22.200
RBX-STUBA-SCD40-1000-316	316 Stainless Steel	10"	10.750	12.750	5.000	1/2	10.020	0.365	22.200
RBX-STUBA-SCD40-1000-CS	Carbon Steel	10"	10.750	12.750	5.000	1/2	10.020	0.365	22.200
RBX-STUBA-SCD40-1200-304	304 Stainless Steel	12"	12.750	15.000	6.000	1/2	12.000	0.375	31.500
RBX-STUBA-SCD40-1200-316	316 Stainless Steel	12"	12.750	15.000	6.000	1/2	12.000	0.375	31.500
RBX-STUBA-SCD40-1200-CS	Carbon Steel	12"	12.750	15.000	6.000	1/2	12.000	0.375	31.500

* Radius measurement in inches of the curved portion of the stub end. It is the value of the physical distance from the centerline of the pipe to the edge of the fitting's curve.

Designed for standard lap joint flanges. Inside corner is square.